

PORTABLE WORKSTATION EVAPORATIVE COOLER

WITH 6 GALLON INTERNAL WATER RESERVOIR THAT
 ALLOWS THE UNIT TO OPERATE APPROXIMATELY
 4 - 6 HOURS WITHOUT BEING CONNECTED
 TO AN EXTERNAL WATER SOURCE



FRONT

**10°F - 30°F OF EVAPORATIVE COOLING
 - PLUS -
 6°F - 8°F OF WIND CHILL COOLING**

EVAPORATIVE COOLING TEMPERATURE DROPS			
AIR TEMPERATURE	RELATIVE HUMIDITY		
	10%	30%	50%
80°	-22°	-16°	-10°
90°	-25°	-18°	-12°
100°	-29°	-21°	-14°
110°	-32°	-23°	-15°



BACK

**PROVIDES COOLING UP TO 25' IN FRONT
 OF THE UNIT OVER A 500 SQ. FT. AREA**

- Water supplied to internal tank from a standard 3/4" water hose or manually through manual fill inlet
- Water level in internal tank controlled by the unit's float valve
- Maintenance free submersible water pump
- 4" thick evaporative media easily accessible for routine cleaning
- Powder coated heavy gauge steel housing
- 17' long, 16 ga. 3-conductor cord with GFCI plug
- Thermally protected, permanently lubricated 2-speed fan motor
- 4" heavy duty casters: 2 locking - 2 non-locking
- Meets OSHA requirements / 1 year limited warranty



UPC	MODEL NUMBER	FAN BLADE	MOTOR HP	UNIT AMPS	CFM		EFFECTIVE SQ. FT.	INTERNAL WATER TANK	DIMENSIONS L x W x H	SHIPPING WEIGHT	List Price
					HIGH	LOW					
869904	EVAP-12	12"	1/8	1.5	3800	2200	500	6 gal.	18.5" x 22" x 29"	51 lbs.	788

**SHIPPABLE
 VIA UPS**



FITS INTO SUV



HEAVY DUTY PORTABLE EVAPORATIVE COOLERS

WITH LARGE INTERNAL WATER RESERVOIRS
THAT ALLOW UNITS TO OPERATE APPROX.
8 HOURS WITHOUT BEING CONNECTED
TO AN EXTERNAL WATER SOURCE



FRONT



BACK

10°F - 30°F OF EVAPORATIVE COOLING
- PLUS -
6°F - 8°F OF WIND CHILL COOLING

EVAPORATIVE COOLING TEMPERATURE DROPS			
AIR TEMPERATURE	RELATIVE HUMIDITY		
	10%	30%	50%
80°	-22°	-16°	-10°
90°	-25°	-18°	-12°
100°	-29°	-21°	-14°
110°	-32°	-23°	-15°

48" belt drive model (EVAP-48) provides cooling up to 150' in front of the unit over a 5000 sq. ft. area

36" variable speed direct drive model (EVAP-36) provides cooling up to 100' in front of the unit over a 3500 sq. ft. area

16" direct drive model (EVAP-16) provides cooling up to 50' in front of the unit over a 1000 sq. ft. area

- Water supplied to internal tank from a standard 3/4" water hose or from optional water tank
- Water level in internal tank controlled by the unit's float valve
- Maintenance free submersible water pump
- 8" thick evaporative media easily accessible for routine cleaning
- Roto-molded corrosion free polyethylene housing
- 20' long, 16 ga. 3-conductor cord with GFCI plug
- Thermally protected, permanently lubricated fan motor
 - Variable speed on 36" unit / 2 speed on 16" & 48" units
- Weather tight fan and pump control switches
- 4" heavy duty casters: 2 locking - 2 non-locking
- UL listed / Meets OSHA requirements / 2 year limited warranty

UNITS THIN ENOUGH TO FIT THROUGH A STANDARD 36" DOOR

UPC	MODEL NUMBER	MOTOR		UNIT AMPS	CFM		EFFECTIVE SQ. FT.	INTERNAL WATER TANK	DIMENSIONS L x W x H	SHIPPING WEIGHT	List Price
		SIZE	HP		HIGH	LOW					
866736	EVAP-16	16"	1/3	7.2	2800	1600	1000	16 gal.	26" x 24" x 50"	105 lbs.	2098
866743	EVAP-36	36"	3/4	9.9	11000 - 6500		3500	46 gal.	62" x 32" x 70"	325 lbs.	4394
870870	EVAP-48	48"	1	13.6	19400	12400	5000	64 gal.	75" x 35" x 84"	497 lbs.	6248

OPTIONAL 60 GALLON WATER TANK



- Polyethylene tank with metal stand
- 4" heavy duty casters:
 - 2 locking - 2 non-locking
- 2 year limited warranty

UPC	MODEL NUMBER	DESCRIPTION	SHIPPING WEIGHT	List Price
866750	ET-60	OPTIONAL 60 GAL. WATER TANK	65 lbs.	1,021